



COMBINED METALS OF CHICAGO

Manufacturing Capabilities Table

| Machine Description | Min Thickness (inches) | Max Thickness (inches) | Min Width (inches) | Max Width (inches) | ID Options On (inches) | ID Options Off (inches) | Max OD On (inches) | Max OD Off (inches) | Max Weight On (pounds) | Max Weight Off (pounds) |
|---------------------|------------------------|------------------------|--------------------|--------------------|------------------------|-------------------------|--------------------|---------------------|------------------------|-------------------------|
| 48 Yoder | 0.004 | 0.125 | 4.75" | 51" | 20, 24 | 20, 24 | 70" | 64" | 33,000 | 33,000 |
| 48 Turret | 0.030 | 0.135 | .52" | 48" | 20, 16 | 20, 16 | 50" | 50" | 30,000 | 22,000 |
| 24RL | 0.002 | 0.03 | .197" | 24" | 20, 16 | 20, 16, 12, 6 | 46" | 46" | 6,000 | 6,000 |
| 24R2 | 0.002 | 0.035 | .315" | 24" | 20, 16 | 20, 16 | 63" | 50" | TBD | 15,000 |
| 24T | 0.035 | 0.07 | .625" | 24" | 20, 16 | 20, 16 | 50" | 48" | 6,000 | 6,000 |

If your requirements fall outside these capabilities, please contact us at cmcinfo@elgiloy.com.

COMBINED METALS OF CHICAGO

2401 W. Grant Avenue

Bellwood IL 60104

800-323-0758

www.combmet.com

REV 2017 04 04